Addendum to Building Permit Application: New Swimming Pool Construction

TOWN OF SOUTHAMPTON

116 Hampton Road, Southampton NY 11968 - (631) 287-5700

Instructions: This addendum must I	be completed in ev	ery respect, typed or pri	nted in ink, and submitted	I with the Applic	ation for Building Permit.		
Owner of Property							
Name of Applicant							
Property Address							
Total Square Footage		Type of Pool	unite 🖵 Oth	ner:			
Of Proposed Pool							
	SQ. FT. Location Undoors Indoors						
Filtration System	(Check 1)	and D.E. Cartridge Filter Area					
	·		_				
	☐ Other: Sq. Ft:						
		I contifue the at the a file		Sow NICE/ANIC	I FO Ctondondo		
Main Filtration Pump		Under (Check 1)	er is properly sized to 500 to 799 Sq. Ft.		800 Sq. Ft. & O),(OF	
main Filtration Fullip		` .	_	,	ουυ 34. Γι. α Ο	VEI	
	• .	eed Under 1 hp	2-Speed/ Size:		☐ Variable Spe	aad	
	2-Speed/	Size: hp	☐ Variable Speed ☐ Variable Speed			eeu	
	■ Variable Speed						
Water Features or Other			Auxiliary				
Auxiliary Load(s)	1.		Pump Type:				
List each with pump type;	0		Auxiliary	Auxiliary Pump Type:			
Single speed auxiliary pumps must be less than	2.		Auxiliary				
one (1) horsepower.	3.			Pump Type:			
Controls	The proposed pool has a time switch or other control mechanism that operates the time system for the time necessary to maintain proper sanitary conditions and then automaticall						
	turns the system off.						
Pipe Diameter	Pipe Diameter = " x 4 ="						
499 Sq. Ft. or less : 1.5" min. 500 Sq. Ft. and over: 2" or							
greater	☐ There will be a length of pipe without bends or turns that is equal to or greater than 4x the pipe diameter installed before the inflow (suction side) of the pump.						
Pipe Fittings	the pipe diameter installed before the lilliow (suction side) of the pump.						
	90 degree turns will be plumbed with low-pressure fittings (Sweep 90's)						
Multiport/Backwash Valve	☐The diameter of this valve will equal the diameter of the pump/pipes ☐ N/A						
Directional Inlets	The diameter of this valve will equal the diameter of the pullip/pipes • 14/A						
Directional finets	☐ The direct	ional inlets shall be	½" diameter or grea	iter	☐ N/A		
Heaters	☐ The heate	☐ The heater shall meet minimum US D.O.E. efficiencies ☐ N/A					
	☐ The heater shall not have a continuously burning pilot light. ☐ N/A						
	☐ A cover shall be fitted and placed on this pool ☐ N/A						
Anti-Entrapment Device	The pool is being installed with Main Drains (Check 1):						
·	If YES, describe both the Safety Vacuum Relief System (SVRS) that conforms to ASME						
	A112.19.17, and the cover that conforms to ANSI/ASME A112.19.8M, and location(s)						
	,				. ()		
I make this Addendum knowi	na full well that	the Town of	Before me, this	day of	, 20)	
Southampton Building & Zoni				~~, ~.	, 2 0		
facts as stated herein to issue							
construction permit.			Notary Public:			_	
Signature	Da	te					